

# METYLAN NORMAL

## Wallpaper Paste for Light, Normal and Heavy Paper Based Wallpaper

### CHARACTERISTICS

- High bonding strength
- Easy to use
- Lump free
- Ready to use in 20 minutes
- Odorless and free of preservative compositions

### SCOPE OF USE

- Ideal for light, normal and heavy paper based wallpaper.

### MIXTURE APPROACH

Application	Mixing Ratio	Quality of cold water to use (Liters)	Approx. Coverage (m <sup>2</sup> )	Approx. Coverage (Rolls)
Pre-pasting	1 : 80	10	100	-
Light paper based WP	1 : 70	8.75	50	10
Middle paper based WP	1 : 60	7.5	40	8
Heavy paper based WP	1 : 50	6.25	30	6

### APPLICATION

#### Wall preparation:

A firm, sound, dry and clean surface is essential. Remove old wallpaper with a suitable wallpaper remover.

#### Mixing:

Sprinkle the contents into the appropriate quantity of water whilst stirring. After 20 minutes re-stir well and the paste is ready for use.

#### Directions:

Apply evenly with brush or roller depending on the absorbency of the wallpaper. Allow paste to soak in thoroughly before proceeding to hang. Heavy wall



coverings may require a second coat. Remove excess paste immediately

### PACKAGING INFORMATION

Packaging Size	Packaging Type	Pieces/ Carton	IDH	Country of Origin
125gr	Folding Box	40	72181	Germany

### STORAGE & SHELF LIFE

This product should be stored (unopened) in its original packaging in a cool, dry place, protected from frost, sparks, flames and direct sunlight. Keep away from children.

Shelf life: 12 months from manufacturing date.

TECHNICAL DATA	
Property	Value
Viscosity:	(mix ratio 1:50 after 30 min): 8.400-9.300 mPas
Moisture content:	Max. 9%
Bulk Density:	310-360 g/l
Solubility:	Approx 20 minutes in cold water

The above instructions are based on thorough trials and on general experience gained in this field. As it is impossible to survey all installation methods and in view of various different working conditions, we cannot, however, claim that the information given is complete. We therefore recommend that tests should be carried out on your own to ensure the greatest possible success. We guarantee a uniform quality standard for this product.

Henkel KGaA